

RECEIVED
CENTRAL FAX CENTER

OCT 30 2007

Serial No. 09/702,218

IN THE CLAIMS

No claims are amended. A listing of the claims as they currently stand in the application are provided for the Examiner's convenience, as follows:

1-6. (CANCELED)

7. (PREVIOUSLY PRESENTED) A system for providing at least near continuous broadcast service to a terrestrial receiver, comprising:

a plurality of satellites, each satellite in an inclined, elliptical, geosynchronous orbit, each satellite providing a portion of time of the at least near continuous broadcast service to the terrestrial receiver, wherein the orbit is characterized by an orbital inclination approximately equal to 50 degrees and an eccentricity approximately equal to 0.13;

wherein the orbit is further characterized by a period approximately equal to 86164 seconds, an altitude at perigee approximately equal to 30305 kilometers, and an altitude at apogee approximately equal to 41268 kilometers.

8-11. (CANCELED)

12. (PREVIOUSLY PRESENTED) A receiver station for receiving at least near continuous broadcast service from a plurality of satellites in an inclined, elliptical, geosynchronous orbit, comprising:

an antenna having a sensitivity characteristic substantially corresponding to the track of the apparent position of each of the satellites,

wherein the receiver antenna comprises a reflector having a focal line and a focal point on the focal line and a head, wherein the head is disposed offset from the focal point, and wherein the head is disposed offset from the focal line, and

wherein the reflector is approximately 18 centimeters in diameter, and the head is disposed approximately 7 inches offset from the focal point and approximately 4 inches offset from the focal line.

13. (ORIGINAL) The receiver station of Claim 12, further comprising a second head disposed substantially at the focal point.

Serial No. 09/702,218

14. (ORIGINAL) The receiver station of Claim 13, wherein the second head receives signals from a geostationary satellite.

15-21. (CANCELED)

22. (PREVIOUSLY PRESENTED) A method of providing at least near continuous broadcast service to a terrestrial receiver, comprising the steps of:

providing a signal having a portion of the continuous broadcast service from at least one of a plurality of satellites at a time, each satellite in an inclined, elliptical, geosynchronous orbit, wherein the orbit is characterized by an orbital inclination approximately equal to 50 degrees and an eccentricity approximately equal to 0.13;

wherein the orbit is further characterized by a period approximately equal to 86164 seconds, an altitude at perigee equal to approximately 30305 kilometers, and an altitude at apogee approximately equal to 41268 kilometers.

23-30. (CANCELED)

31. (PREVIOUSLY PRESENTED) A method of receiving at least near continuous broadcast service at a terrestrial receiver, comprising the steps of:

receiving a signal having a portion of the continuous broadcast service from at least one of a plurality of satellites at a time, each satellite in an inclined, elliptical, geosynchronous orbit, wherein the orbit is characterized by an orbital inclination equal to 50 degrees and an eccentricity equal to 0.13;

wherein the orbit is further characterized by a period equal to 86164 seconds, an altitude at perigee equal to 30305 kilometers, and an altitude at apogee equal to 41268 kilometers.

32-44. (CANCELED)

Serial No. 09/702,218

45. (PREVIOUSLY PRESENTED) A satellite system comprising:
at least one satellite in a geostationary orbit;
a plurality of satellites, each in an inclined, elliptical geosynchronous orbit;
a receiver station antenna that can communicate with said at least one satellite and at least one of said plurality of satellites during an active period without tracking, and
a gateway having a tracking antenna to track said plurality of satellites;
wherein each satellite of the plurality of satellites is an active satellite during an active period, and a track of the apparent position of each active satellite relative to the receiver station antenna is substantially closed loop and when an active satellite is nearing the end of the active period, the apparent position of the active satellite substantially overlaps another one of the plurality of satellites that is beginning the active period.

46. (CANCELED)

47. (PREVIOUSLY PRESENTED) The satellite system of Claim 45, wherein a beamwidth of said tracking antenna of said gateway is sufficient to encompass both said active one and said another one of said plurality of satellites.

48. (PREVIOUSLY PRESENTED) The satellite system of Claim 45, wherein apparent positions of the plurality of satellites are spatially separated from the apparent position of the at least one satellite in geostationary orbit to avoid interference.

49. (PREVIOUSLY PRESENTED) The satellite system of Claim 48, wherein the angular separation between the plurality of satellites and at least one satellite in geostationary orbit is at least thirty degrees.

50-52. (CANCELED)

53. (PREVIOUSLY PRESENTED) The system of claim 7, wherein the plurality of satellites augments at least one legacy satellite in a geostationary orbit.

Serial No. 09/702,218

54. (PREVIOUSLY PRESENTED) The receiver station of claim 12, wherein each of the plurality of satellites provides a portion of time of the at least near continuous broadcast service.

55. (PREVIOUSLY PRESENTED) The receiver station of claim 54, wherein the plurality of satellites augments at least one legacy satellite in a geostationary orbit.

56. (PREVIOUSLY PRESENTED) The method of claim 22, wherein the plurality of satellites augments at least one legacy satellite in a geostationary orbit.

57. (PREVIOUSLY PRESENTED) The method of claim 31, wherein the plurality of satellites augments at least one legacy satellite in a geostationary orbit.

58. (PREVIOUSLY PRESENTED) The satellite system of claim 45, wherein the plurality of satellites augments at least one legacy satellite in a geostationary orbit.